

COMPETITIVE COMPARISON				
MODEL		Kubota B2650	John Deere 2025R	Mahindra Max 26XL HST
Engine	Manufacturer	Kubota	Yanmar	Mitsubishi
	Type	Diesel	Diesel	Diesel
	Gross Engine (*SAE J1995) HP (kw)	26.0 (19.4)*	23.9 (17.8)	25.6 (19.1)
	PTO (*OECD 2) HP (kw)	19.5 (14.5)*	18.0 (13.4)	20 (14.9)
	Rated Engine Speed rpm	2500	3200	2600
	Cylinders/Displacement cu.in. (liters)	3 / 77.0 (1.261)	3 / 77.0 (1.267)	3 / 80.4 (1.318)
	Engine Torque @ rated speed ft./lb. (N/m)	60.48 (8.3)	39.09 (53)	-
	Fuel Tank Capacity, ROPS US Gal. (L)	7.1 (27.0)	6.3 (23.8)	6.1 (23)
	Fuel Tank Capacity, CAB US Gal. (L)	7.4 (28.0)	-	6.1 (23)
Electrical	Battery Size (CCA)	430	500	45AH
	Alternator (12 volt, amp)	14.5 A - dynamo 60 A	40	50
Transmission	Transmission	Hydrostatic - 3 Range	Hydrostatic - 2 Range	Hydrostatic - 2 Range
	Brakes	Multi Wet Disc	Wet Disc	Wet Disc
	Steering	Power	Power	Power
	Axle Capacity Front, lb. (kg)	2205 (1000)	1349 (612)	-
	Rear, lb. (kg)	2205 (1000)	2425 (1100)	-
Hydraulics	Remote Control Valves Available	2, Optional	2, Optional	1, Optional
	Main Pump Flow gpm (l/m)	5 (18.9)	3.5 (13.25)	5.8 (21.9)
	Total Flow GPM gpm (l/m)	8.7 (33.1)	7.0 (26.5)	8.5 (32.2)
	Control Type	Position	Position	Position
3-point Hitch	Type	Cat. I	Limited Cat. I	Cat. I
	Lower Link Adjustment	Telescopic	Check chains	Check Chains
	Lift Capacity (24-in. behind link arms) lb. (kg)	1676 (760)	882 (400)	-
	Lift Capacity @ lift links ends lb. (kg)	2139 (970)	N/P	2205 (1000)
Power Take-Off (PTO)	Standard for ROPS	Rear 540 / Mid 2500	Rear 540 / Mid 2100	Rear 540 / Mid 2000
	Standard for CAB	Rear 563 / Mid 2500	-	Rear 540 / Mid 2000
	Control	Independent	Independent	Live
Dimensions	Wheelbase in. (mm)	65.6 (1666)	63 (1600)	-
	Height, Top of ROPS in. (mm)	88.4 (2245)	-	84.3 (2140)
	Height, Top of CAB in. (mm)	84.6 (2150)	-	82 (2082)
	Front Tread in. (mm)	36.8 (935)	37.5 (953)	-
	Min. ground clearance in. (mm)	14.6 (370)	12.5 (316)	-
	Turning Radius w/ Brake ft (m)	6.9 (2.1)	8.7 (2.65)	6.6 (2.0)
	Tractor Weight, ROPS lb (kg)	1786 (810)	1793 (813.5)	1863 (845)
	Tractor Weight, CAB lb (kg)	2293 (1040)	-	2082 (944)
	Cab Available?	Yes	Not Available	Yes
Standard Tires	Front	7.0-12 ; Ag	23x8.50-12 ; Industrial	23x8.5-12 ; Industrial
	Rear	12.4-16 ; Ag	12-16.5 ; Industrial	12x16.5 ; Industrial

N/A = Not Available  
N/P = Not Published

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.