

Kubota Tractor Loader Backhoe B26 TLB



COMPETITIVE COMPARISON

FEATURE		Kubota B26 TLB	Terramite T7	Waldon Digmaster
Engine	Engine gross power hp	26.0	25	20
	PTO power hp	19.5	No PTO	No PTO
	No. of cylinders	3	3	3
	Total displacement cu. in.	68.5	38	NP
	Emissions Tier Level (EPA)	Tier 4 Interim	Not Published	Not Published
	Fuel tank capacity gal.	8.2	9.5	5.2
Transmission	Type	HST (3 ranges)	HST (1 range)	HST (1 range)
	4 Wheel Drive	Standard	No	No
	Maximum Travel Speed mph	11.1	INA	NP
	Brake	Multi Wet Disc	INA	NP
PTO	Standard	Rear	No PTO	No PTO
	Speeds @ RPM	540 @ 2768	N/A	N/A
	Control	Hydraulic Independent	N/A	N/A
Tires	R4 Front Rear	23 x 8.50 - 14	23 x 10.5 - 12	20.5 x 8 x 10
		12.4 - 16	31 x 15.5 - 15	31 x 15.5 - 15
	AG Front Rear	23 x 8.50 - 14	N/A	N/A
		12.4 - 16	Available	N/A
	Turf Front Rear	24x 8.50 - 14	Available	N/A
		13.6 - 16	Available	N/A

Kubota Tractor Loader Backhoe B26 TLB



COMPETITIVE COMPARISON

MODEL		Kubota B26 TLB	Terramite T7	Waldon Digmaster
Hydraulic System	Pump capacity	11.1	8	8.4
	3-Point Hitch lift capacity @ 24" behind lift point	1676	No 3-Point Hitch	No 3-Point Hitch
	Position Control	Standard	N/A	N/A
	Power steering	Hydrostatic	Hydrostatic	Hydrostatic
Loader	Loader Quick Coupler	Standard	Option	N/A
	Loader Bucket Capacity cu. ft.	9.5	9.0	10.5
	Auxiliary Hydraulic Flow gpm	6.9	NP	N/A
	Breakout Force, Pivot Pin lbs.	2343	4400	2200
	Lift Capacity, Pivot Pin lbs.	1301	1700	1500
	Protected Hoses	Standard	N/A	N/A
	Mechanical Spill Guard	Standard	N/A	N/A
	Side Position Lever w/ Arm Rest	Standard	N/A	N/A
Backhoe	Quick Attach Backhoe	Standard	No	No
	Maximim Digging Depth	8' 4"	8' 8"	8' 0"
	Bucket Breakout Force lbs.	4,210	3100	4100
	Dipper Breakout Force lbs.	2,123	2800	2500
	Auxiliary Hydraulic Flow gpm	6.9	N/A	N/A
	Arch Type Boom	Standard	Standard	N/A
	Bucket QC Option	Available	Available	N/A
	Thumb Option	Available	N/A	N/A

Kubota Tractor Loader Backhoe B26 TLB



COMPETITIVE COMPARISON

MODEL		Kubota B26 TLB	Terramite T7	Waldon Digmaster
Features	ROPS / FOPS Canopy	Standard	4 - Post ROPS	Standard
	Side Position Throttle & Key	Standard	N/A	N/A
	Turn In Place Seat	Standard	N/A	N/A
	Tilt Steering Wheel	Standard	N/A	N/A
	Retractable Seat Belt	Standard	N/A	N/A
	Spark Arrestor Muffler	Standard	INA	INA
Dimensions	Wheelbase in.	62.2	61	59.96
	Min. ground clearance in.	11.3	INA	8.0
	Transport Length in.	201.9	177	173.5
	Overall height in.	89.5	82	82.65
	Overall width in.	60	58	62.9
	Weight lbs.	4,001	4180	3285

Comparisons of specifications are based on the latest data available to Kubota at the time of publication.

Kubota reserves the right to change specifications relating to its products without notice.

Competitive information in this section was obtained from competitive websites and product brochures, and is correct to the best of our knowledge.