

Kubota Tractor B3350SUHSD



COMPETITIVE COMPARISON				
MODEL		Kubota B3350SUHSD	John Deere 2032R	
Engine	Manufacturer	Kubota	Yanmar	
	Type	Diesel	Diesel	
	Gross Engine (*SAE J1995)	HP (kw)	33.0 (24.6)*	31.6 (23.3)
	PTO (*OECD 2)	HP (kw)	27.0 (20.1)*	23.5 (17.5)
	Rated Engine Speed	rpm	2500	2500
	Cylinders/Displacement	cu.in. (liters)	4 / 91.5 (1.498)	3 / 100.2 (1.642)
	Engine Torque @ rated speed	ft./lb. (N/m)	76.3 (10.55)	63.0 (85.4)
	Fuel Tank Cap	US Gal. (L)	7.1 (27.0)	7.1 (27.0)
Electrical	Battery Size (CCA)	430	500	
	Alternator (12 volt, amp)	60	40	
Transmission	Transmission	Hydrostatic - 3 Range	Hydrostatic - 2 Range	
	Brakes	Multi Wet Disc	Wet Disc	
	Steering	Power	Power	
	Axle Capacity Rear, lb. (kg)	Front, lb. (kg)	2205 (1000) 2205 (1000)	1940 (880) 2426 (1100)
Hydraulics	Remote Control Valves Available	2, Optional	2, Optional	
	Main Pump Flow	gpm (l/m)	5.0 (18.9)	5 (18.9)
	Total Flow GPM	gpm (l/m)	8.7 (33.1)	10.5 (39.6)
	Control Type	Position	Position	
3-point Hitch	Type	Cat. I	Cat. I	
	Lower Link Adjustment	Telescopic	N/P	
	Lift Capacity (24-in. behind link arms) lb. (kg)	1676 (760)	1250 (540)	
	Lift Capacity @ lift links ends lb. (kg)	2139 (970)	N/P	
Power Take-Off (PTO)	Standard	Rear 540	Rear 540 / Mid 2100	
	Control	Independent	Independent	
	Clutch	N/A	-	
Dimensions	Wheelbase	in. (mm)	65.6 (1666)	65.2 (1655)
	Height	in. (mm)	88.4 (2245)	N/P
	Front Tread	in. (mm)	36.8 (935)	32.7 (830)
	Min. ground clearance	in. (mm)	14.6 (370)	13 (330)
	Turning Radius w/ Brake	ft (m)	6.9 (2.1)	7.5 (2.3)
	Tractor Weight	lb (kg)	1874 (850)	1973 (895)
Standard Tires	Front	7.0-12 ; Ag	24x8.5-14 ; Turf	
	Rear	12.4-16 ; Ag	36x14.0-15 ; Turf	

N/A = Not Available N/P = Not Published

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.