



COMPETITIVE COMPARISON						
FEATURE		Kubota L3560		John Deere 3033R		
		Gear 4WD	HST 4WD	Gear 4WD	HST 4WD	
Engine	Engine manufacturer	Kubota		Yanmar		
	Engine	D1803		3TNV88C		
	EPA Emission level	Tier 4		Tier 4		
	Gross Engine (*SAE J1995)	HP (kw)	37.0 (27.6)*		32.2 (23.7)	
	Engine net power (*SAE J1349)	HP (kw)	35.0 (26.1)*		N/P	
	PTO power (*OECD 2)	HP (kw)	29.5 (22.0)*	28.0 (20.9)*	24.8 (18.5)	24.3 (18.1)
	No. of cylinders	3		3		
	Injection type	Indirect Injection		Direct Injection		
	Total displacement	cu.in. (cc)	100.5 (1647)		100 (1640)	
	Rated revolution		2700	2600	2600	
	Aspiration	Natural		Natural		
	Alternator amps	ROPS: 40 // CAB: 60		75		
	Fuel tank capacity	gal. (l)	13.5 (51)		ROPS: 13.5 (51) // CAB: 11.8 (44.7)	
	Air cleaner	Dual Element		Dual Element		
	Drive Train	Transmission	DT- 8F/8R 12F/8R	GST- 3-Range With Hydro Dual Speed Infinitely Variable	12F/12R PowrReverser	HST - 3 Range
Brake		Multi-plate wet disc		Multi-plate wet disc		
PTO		Live Independent		Independent		
Engagement method		Electro-hydraulic		Electro-hydraulic		
PTO speeds @ RPM		540 @ 2550	540 @ 2425	540		
Control type		Position (Optional Draft and Mixed)		Position		
Mid PTO		Optional		Optional		
Cruise Control		N/A	Standard	N/A	Standard	
Creep speed		Optional	N/A	N/P		
Front Axle		Bevel gear		Bull Gear		
Power steering		Hydrostatic power steering		Hydrostatic power steering		
Standard Tires	Front	7.2-16 ; Ag		7-14 ; Ag		
	Rear	12.4-24 ; Ag		11.2-24 ; Ag		
Hydraulic System	Implement Pump capacity	gpm (l/m)	8.3 (31.5)	8.0 (30.3)	8.6 (32.5)	
	Power steering pump	gpm (l/m)	4.9 (18.6)	4.7 (17.9)	5.9 (22.3)	
	Total flow	gpm (l/m)	13.2 (50.1)	12.7 (48.1)	14.4 (54.5)	
	Category hitch	Cat. I		Cat. I		
	3-Point Hitch lift capacity @ 24" behind lift point lb. (kg)	2646 (1200)		2200 (998)		
	Rear remote hydraulic valves	Up to 3 rear remotes		Up to 4 rear remotes		
Dimensions	Telescoping link ends	Standard		N/P		
	Wheelbase	in. (mm)	71.1 (1805)		68.0 (172.7)	
	Tread	Front	in. (mm)	45.5 (1155)		44.9 (1140)
		Rear	in. (mm)	47.2 (1200) - 51.2 (1300) - 54.5 (1385) - 58.3 (1480)		40.6 (1031)
	Overall Length w/ 3-Point Hitch	in. (mm)	124.4 (3160)		N/P	
	Overall Height	in. (mm)	ROPS: 97.2 (2470) // CAB: 90.6 (2300)		ROPS: 93.3 (2370) // CAB: 85.0 (2159)	
	Overall Width (min. tread)	in. (mm)	59.8 (1520)		N/P	
	Min. ground clearance	in. (mm)	13.5 (345)		12.2 (310)	
	Min. turning radius w/ brake	ft. (m)	8.9 (2.7)		8.8 (2.7)	
	Factory Cab Option	Optional		Optional		
Weight	lbs. (kg)	DT: 3340 (1515) GST: 3384 (1535)	HST: 3483 (1580) HSTC: 3880 (1760)	ROPS: 2900 (1315) CAB: 3570 (1619)		

N/A = Not Available N/P = Not Published

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



FEATURE		COMPETITIVE COMPARISON												
		Kubota L4060				John Deere 3039R				Mahindra 3540				
		Gear 4WD		HST 4WD		Gear 4WD		HST 4WD		Gear 4WD		HST 4WD		
Engine	Engine manufacturer	Kubota				Yanmar				Mahindra				
	Engine	V2403				3TNV86CT				N/P				
	EPA Emission level	Tier 4				Tier 4				Tier 4				
	Gross Engine (*SAE J1995) HP (kw)	42 (31.3)*				38.8 (28.5)				40.0 (29.8)				
	Engine net power (*SAE J1349) HP (kw)	40 (29.8)*				N/P				N/P				
	PTO power (*OECD 2) HP (kw)	34.0 (25.4)*		32.5 (24.2)*		31.6 (23.6)		31.1 (23.2)		30.0 (23.1)		30.25 (22.7)		
	No. of cylinders	4				3				4				
	Injection type	Indirect Injection				Direct Injection				Direct Injection				
	Total displacement cu.in. (cc)	122.0 (1999)				95.7 (1570)				166.64 (2730)				
	Rated revolution	2700		2600		2600				2800				
	Aspiration	Natural				Turbocharged				Natural				
	Alternator amps	ROPS: 40 // CAB: 60				75				ROPS: 45 // CAB: 120				
	Fuel tank capacity gal. (l)	13.5 (51)				ROPS: 13.5 (51) // CAB: 11.8 (44.7)				ROPS: 11.3 (42.8) // CAB: 14.5 (54.9)				
Air cleaner	Dual element				Dual Element				N/P					
Drive Train	Transmission	DT- 8F/8R GST- 12F/8R		3-Range With Hydro Dual Speed Infinitely Variable		12F/12R PowrReverser		HST - 3 Range		12F/12R PowrReverser		HST - 3 Range		
	Brake	Multi-plate wet disc				Multi-plate wet disc				Multi-plate wet disc				
	PTO	Live Independent				Independent				Independent				
	Engagement method	Electro-hydraulic				Electro-hydraulic				N/P				
	PTO speeds @ RPM	540 @ 2550		540 @ 2476		540 @ 2600				540 @ 2404				
	Control type	Position (Optional Draft and Mixed)				Position				Position				
	Mid PTO	Optional				Optional				Optional				
	Cruise Control	N/A		Standard		N/A		Standard		N/P				
	Creep speed	Optional		N/A		SpeedMatch optional		N/A		N/P				
	Front Axle	Bevel gear				Bull gear				N/P				
Power steering	Hydrostatic power steering				Hydrostatic power steering				Hydrostatic power steering					
Standard Tires	Front	8.3-16 ; Ag				7-14 ; Ag				9.5-16 ; Ag				
	Rear	14.9-24 ; Ag				11.2-24 ; Ag				14.9-24 ; Ag				
Hydraulic System	Implement Pump capacity gpm (l/m)	9.8 (37.0)		9.4 (35.6)		8.6 (32.5)				11.0 (41.6)				
	Power steering pump gpm (l/m)	4.9 (18.6)		4.7 (17.9)		5.9 (22.3)				5.0 (18.9)				
	Total flow gpm (l/m)	14.7 (55.6)		14.1 (53.5)		14.4 (54.5)				15.0 (56.8)				
	Category hitch	Cat. I				Cat. I				Cat. I				
	3-Point Hitch lift capacity @ 24" behind lift point lb. (kg)	2756 (1250)				2200 (998)				3090 (1401.6), @ pin				
	Rear remote hydraulic valves	Up to 3 rear remotes				Up to 3 rear remotes				1, standard				
	Telescoping link ends	Standard				Optional				Standard				
Stabilizers	Telescoping stabilizers				Standard				N/P					
Dimensions	Wheelbase in. (mm)	74.6 (3085)				38.0 (172.7)				N/P				
	Tread	Front in. (mm)	45.5 (1155)				44.9 (1140)				N/P			
		Rear in. (mm)	50.6 (1285) - 56.5 (1435) - 60.2 (1530)				40.6 (1031)				N/P			
	Overall Length w/ 3-Point Hitch in. (mm)	129.5 (3290)				N/P				128.9 (3274)				
	Overall Height in. (mm)	ROPS: 97.6 (2480) // CAB: 91.1 (2315)				ROPS: 93.3 (2370) // CAB: 85.0 (2159)				ROPS: 98.7 (2492) // CAB: 89.8 (2280)				
	Overall Width (min. tread) in. (mm)	66.5 (1690)				N/P				73.7 (1871)				
	Min. ground clearance in. (mm)	14.4 (360)				12.2 (310)				N/P				
	Min. turning radius w/ brake ft. (m)	8.9 (2.7)				8.8 (2.7)				10.3 (3.2)				
Factory Cab Option	Optional				Optional				Optional					
Weight lbs. (kg)	DT: 3571 (1620)		HST: 3714 (1685)		ROPS: 2900 (1315)				PST: 4367 (1980.8)		PSTC: 5167 (2343.7)			
	GST: 3616 (1640)		HSTC: 4089 (1855)		CAB: 3570 (1619)				HST: 4817 (2185)		HSTC: 5617 (2547.8)			

N/A = Not Available N/P = Not Published

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



FEATURE		Kubota L4760		John Deere 3046R		John Deere 4044R		Mahindra 3550		
		Gear 4WD	HST 4WD	Gear 4WD	HST 4WD	Gear 4WD	HST 4WD	Gear 4WD	HST 4WD	
Engine	Engine manufacturer	Kubota		Yanmar		Yanmar		Mahindra		
	Engine	V2403		4TNV86CHT		4TNV88C		N/P		
	EPA Emission level	Tier 4		Tier 4		Tier 4		Tier 4		
	Gross Engine (*SAE J1995) HP (kw)	49.0 (36.6)*		45.3 (33.3)		43.1 (31.7)		49.0 (36.5)		
	Engine net power (*SAE J1349) HP (kw)	47.0 (35.1)*		N/P		N/P		N/P		
	PTO power (*OECD 2) HP (kw)	41.0 (30.6)*	39.5 (29.5)*	36.6 (27.3)		34.5 (25.7)		40.0 (29.8)	39.5 (29.4)	
	No. of cylinders	4		3		4		4		
	Injection type	Indirect Injection		Direct Injection		Direct Injection		Direct Injection		
	Total displacement cu.in. (cc)	134.1 (2197)		95.7 (1570)		133.5 (2189)		166.64 (2730)		
	Rated revolution	2700	2600	2600		2600		2800		
	Aspiration	Natural		Turbocharged		Natural		Natural		
	Alternator amps	ROPS: 40 // CAB: 60		75		75		ROPS: 45 // CAB: 120		
	Fuel tank capacity gal. (l)	13.5 (51)		ROPS: 13.5 (51) // CAB: 11.8 (44.7)		ROPS: 13.0 (50) // CAB: 13.8 (52.2)		ROPS: 11.3 (42.8) // CAB: 14.5 (54.9)		
	Air cleaner	Dual element		Dual element		Dual Element		N/P		
Drive Train	Transmission	12F/8R	3-Range With Hydro Dual Speed Infinitely Variable	12F/12R	HST - 3 Range	12F/12R PowrReverser	HST: 3-Range, Optional	12F/12R PowrReverser	HST - 3 Range	
	Brake	Multi-plate wet disc		Multi-plate wet disc		Multi-plate wet disc		Multi-plate wet disc		
	PTO	Live Independent		Independent		Independent		Independent		
	Engagement method	Electro-hydraulic		Electro-hydraulic		Electro-hydraulic		N/P		
	PTO speeds @ RPM	540 @ 2550	540 @ 2475	540 @ 2600		540 @ 2600		540 @ 2404		
	Control type	Position (Optional Draft and Mixed)		Position		Position		Position		
	Mid PTO	Optional		Optional		N/A		Optional		
	Cruise Control	N/A	Standard	N/A	Standard	N/A	Standard	N/P		
	Creep speed	Optional	N/A	SpeedMatch, optional	N/A	Standard	N/A	N/P		
	Front Axle	Bevel gear		Bull Gear		Planetary Gear		N/P		
	Power steering	Hydrostatic power steering		Hydrostatic power steering		Hydrostatic power steering		Hydrostatic power steering		
Standard Tires	Front	8.3-16 ; Ag		7-14 ; Ag		8-16 ; Ag		9.5-20 ; Ag		
	Rear	14.9-24 ; Ag		11.2-24 ; Ag		13.6-28 ; Ag		16.9-24 ; Ag		
Hydraulic System	Implement Pump capacity gpm (l/m)	9.8 (37.0)	9.4 (35.6)	8.6 (32.5)		10.2 (38.7)		11.0 (41.6)		
	Power steering pump gpm (l/m)	4.9 (18.6)	4.7 (17.9)	5.9 (22.3)		5.7 (21.5)		5.0 (18.9)		
	Total flow gpm (l/m)	14.7 (55.6)	14.1 (53.5)	14.4 (54.5)		15.9 (60.2)		15.0 (56.8)		
	Category hitch	Cat. I		Cat. I		Cat. I		Cat. I		
	3-Point Hitch lift capacity @ 24" behind lift point lb. (kg)	2756 (1250)		2200 (998)		2500 (1135)		3090 (1401.6), @ pin		
	Rear remote hydraulic valves	Up to 3 rear remotes		Up to 4 rear remotes		Up to 3 rear remotes		1, standard		
	Telescoping link ends	Standard		N/P		N/P		Standard		
Stabilizers	Telescoping stabilizers		N/P		N/P		N/P			
Dimensions	Wheelbase in. (mm)	74.6 (1895)		68.0 (172.7)		73.0 (185.5)		N/P		
	Tread	Front in. (mm)	51.2 (1300)		44.9 (1140)		53.8 (1367)		N/P	
		Rear in. (mm)	50.6 (1285) - 56.5 (1435) - 60.2 (1530)		40.6 (1031)		54.0 (1372)		N/P	
	Overall Length w/ 3-Point Hitch in. (mm)	129.5 (3290)		N/P		N/P		128.9 (3274)		
	Overall Height in. (mm)	ROPS: 97.6 (2480) // CAB: 91.9 (2335)		ROPS: 93.3 (2370) // CAB: 85.0 (2159)		ROPS: 100.2 (2546) // CAB: 97.4 (2474)		ROPS: 98.7 (2492) // CAB: 89.8 (2280)		
	Overall Width (min. tread) in. (mm)	66.5 (1690)		N/P		N/P		73.7 (1871)		
	Min. ground clearance in. (mm)	14.4 (360)		12.2 (310)		14.8 (377)		N/P		
	Min. turning radius w/ brake ft. (m)	8.9 (2.7)		8.8 (2.7)		9.17 (2.8)		10.3 (3.2)		
Factory Cab Option	Optional		Optional		Optional		Optional			
Weight lbs. (kg)	GST: 3660 (1660) HST: 3759 (1705) HSTC: 4134 (1875)		ROPS: 2900 (1315) CAB: 3570 (1619)		ROPS: 3770 (1710) CAB: 4675 (2120)		PST: 4939 (2240.3) PSTC: 5739 (2603.2) HST: 5389 (2444.4) HSTC: 6189 (2807.3)			

N/A = Not Available N/P = Not Published

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or rebalanced in any country other than the country for which the Product(s) were designed or manufactured.

COMPETITIVE COMPARISON

FEATURE		Kubota L5060	John Deere 4052R		Mahindra 3550		
		Gear 4WD	Gear 4WD	HST 4WD	Gear 4WD	HST 4WD	
Engine	Engine manufacturer	Kubota	Yanmar		Mahindra		
	Engine	V2403	4TNV86CT-MJT		N/P		
	EPA Emission level	Tier 4	Tier 4		Tier 4		
	Gross Engine (*SAE J1995)	HP (kw)	52.0 (38.8)*	50.8 (37.9)		49.0 (36.5)	
	Engine net power (*SAE J1349)	HP (kw)	50.0 (37.3)*	N/P		N/P	
	PTO power (*OECD 2)	HP (kw)	44.0 (32.8)*	42.2 (31.4)		40.0 (29.8)	39.5 (29.4)
	No. of cylinders		4	4		4	
	Injection type		Indirect Injection	Direct Injection		Direct Injection	
	Total displacement	cu.in. (cc)	148.5 (2434)	127.6 (2091)		166.64 (2730)	
	Rated revolution		2700	2600		2800	
	Aspiration		Turbocharged	Turbocharged		Natural	
	Alternator amps		45	75		ROPS: 45 // CAB: 120	
	Fuel tank capacity	gal. (l)	13.5 (51)	ROPS: 13.0 (49.2) // CAB: 13.8 (52.2)		ROPS: 11.3 (42.8) // CAB: 14.5 (54.9)	
	Air cleaner		Dual element	Dual element		N/P	
Drive Train	Transmission	12F/8R	12F/12R PowReverser	3 Range Infinitely Variable	12F/12R PowReverser	HST - 3 Range	
	Brake	Multi-plate wet disc	Multi-plate wet disc		Multi-plate wet disc		
	PTO	Live Independent	Independent		Independent		
	Engagement method	Electro-hydraulic	Electro-hydraulic		N/P		
	PTO speeds @ RPM	540 @ 2550	540 @ 2600		540 @ 2404		
	Control type	Position (Optional Draft and Mixed)	Position		Position		
	Mid PTO	Optional	N/A		Optional		
	Cruise Control	N/A	N/A	Standard	N/P		
	Creep speed	Optional	Standard	N/A	N/P		
	Front Axle	Bevel gear	Planetary gear		N/P		
	Power steering	Hydrostatic power steering	Hydrostatic power steering		Hydrostatic power steering		
Standard Tires	Front	9.5-16 ; Ag	8-16 ; Ag		9.5-20 ; Ag		
	Rear	14.9-26 ; Ag	14.9-24 ; Ag		16.9-24 ; Ag		
Hydraulic System	Implement Pump capacity	gpm (l/m)	9.8 (37.0)	10.2 (38.7)		11.0 (41.6)	
	Power steering pump	gpm (l/m)	4.9 (18.6)	5.7 (21.5)		5.0 (18.9)	
	Total flow	gpm (l/m)	14.7 (55.6)	15.9 (60.2)		15.0 (56.8)	
	Category hitch		Cat. I & II	Cat. I		Cat. I	
	3-Point Hitch lift capacity @ 24" behind lift point lb. (kg)		2976 (1350)	2500 (1135)		3090 (1401.6), @ pin	
	Rear remote hydraulic valves		Up to 3 rear remotes	Up to 5 rear remotes		1, standard	
	Telescoping link ends		Standard	N/P		Standard	
Stabilizers		Telescoping stabilizers	N/P		N/P		
Dimensions	Wheelbase	in. (mm)	75.4 (1915)	73.0 (185.4)		N/P	
	Tread	Front	in. (mm)	52.8 (1340)	53.8 (1367)		N/P
		Rear	in. (mm)	52.2 (1325) - 56.3 (1430)	54.0 (1372)		N/P
	Overall Length w/ 3-Point Hitch	in. (mm)	135.0 (3430)	N/P		128.9 (3274)	
	Overall Height	in. (mm)	98 (2490)	ROPS: 100.2 (2546) // CAB: 97.4 (2474)		ROPS: 98.7 (2492) // CAB: 89.8 (2280)	
	Overall Width (min. tread)	in. (mm)	67.3 (1710)	N/P		73.7 (1871)	
	Min. ground clearance	in. (mm)	15.4 (392)	14.8 (377)		N/P	
	Min. turning radius w/ brake	ft. (m)	9.2 (2.8)	9.2 (2.8)		10.3 (3.2)	
	Factory Cab Option		N/A	Optional		Optional	
Weight	lbs. (kg)		ROPS: 3770 (1710) CAB: 4675 (2120)		PST: 4939 (2240.3) HST: 5389 (2444.4)	PSTC: 5739 (2603.2) HSTC: 6189 (2807.3)	

N/A = Not Available N/P = Not Published

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/ KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



COMPETITIVE COMPARISON

FEATURE		Kubota L5460		Mahindra 2555		
		HST 4WD		Gear 4WD	HST 4WD	
Engine	Engine manufacturer	Kubota		Mahindra		
	Engine	V2403		N/P		
	EPA Emission level	Tier 4		Tier 4		
	Gross Engine (*SAE J1995)	HP (kw)	56.0 (41.8)*	55.0 (41.0)		
	Engine net power (*SAE J1349)	HP (kw)	54.0 (40.3)*	N/P		
	PTO power (*OECD 2)	HP (kw)	46.5 (34.7)*	44.5 (32.7)	42.4 (31.6)	
	No. of cylinders		4	3		
	Injection type		Indirect Injection	Direct Injection		
	Total displacement	cu.in. (cc)	148.5 (2434)	161.5 (2648)		
	Rated revolution		2600	2300		
	Aspiration		Turbocharged	Turbocharged		
	Alternator amps		ROPS: 45 // CAB: 60	90		
	Fuel tank capacity	gal. (l)	13.5 (51)	16.0 (60.6)		
	Air cleaner		Dual element	N/P		
	Drive Train	Transmission	3-Range With Hydro Dual Speed Infinitely Variable		12F/12R	3-Range
Brake		Multi-plate wet disc		Wet disc		
PTO		Live Independent		Independent		
Engagement method		Electro-hydraulic		N/P		
PTO speeds @ RPM			540 @ 2400	540 @ 2300		
Control type		Position (Optional Draft and Mixed)		Position		
Mid PTO			Optional	N/P		
Cruise Control			Standard	N/P		
Front Axle			Bevel gear	N/P		
Power steering			Hydrostatic power steering	Hydrostatic power steering		
Standard Tires		Front	9.5-16 ; Ag		9.5-16 ; Ag	
		Rear	14.9-26 ; Ag		14.9-24 ; Ag	
Hydraulic System		Implement Pump capacity	gpm (l/m)	9.4 (35.6)	9.5 (36.0)	9.7 (36.7)
		Power steering pump	gpm (l/m)	4.7 (17.9)	4.5 (17.0)	5.0 (18.9)
		Total flow	gpm (l/m)	14.1 (53.5)	14.0 (53.0)	14.7 (55.6)
	Category hitch		Cat. I & II	Cat. I		
	3-Point Hitch lift capacity @ 24" behind lift point	lb. (kg)	2976 (1350)	3314 (1503.2), @ pin		
	Rear remote hydraulic valves		Up to 3 rear remotes	1 standard, 2 optional		
	Telescoping link ends		Standard	Optional		
Dimensions	Stabilizers		Telescoping stabilizers	Telescoping stabilizers		
	Wheelbase	in. (mm)	75.4 (1915)	N/P		
	Tread	Front	in. (mm)	52.8 (1340)	N/P	
		Rear	in. (mm)	52.2 (1325) - 56.3 (1430)	N/P	
	Overall Length w/ 3-Point Hitch	in. (mm)	135.0 (3430)	134.1 (3406)		
	Overall Height	in. (mm)	ROPS: 98.0 (2490) // CAB: 92.5 (2350)	102 (2590)		
	Overall Width (min. tread)	in. (mm)	67.3 (1710)	71.1 (1807)		
	Min. ground clearance	in. (mm)	15.4 (392)	N/P		
	Min. turning radius w/ brake	ft. (m)	9.2 (2.8)	11 (3.4)		
	Factory Cab Option		Optional	Optional		
Weight	lbs. (kg)	HST: 4023 (1825) HSTC: 4376 (1985)	ROPS: 4056 (1839.8) // CAB: 4299 (1950)			

N/A = Not Available N/P = Not Published

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



COMPETITIVE COMPARISON

FEATURE		Kubota L6060	John Deere 4066R		Mahindra 2555		
		HST 4WD	Gear 4WD	HST 4WD	Gear 4WD	HST 4WD	
Engine	Engine manufacturer	Kubota	John Deere		Mahindra		
	Engine	V2403	Yanmar 4TNV86CHT-MJT		N/P		
	EPA Emission level	Tier 4	Tier 4		Tier 4		
	Gross Engine (*SAE J1995) HP (kw)	62.0 (46.3)*	65.9 (48.5)		55.0 (41.0)		
	Engine net power (*SAE J1349) HP (kw)	60 (44.8)*	N/P		N/P		
	PTO power (*OECD 2) HP (kw)	53.0 (39.5)*	54.0 (40.2)	52.0 (38.7)	44.5 (32.7)	42.4 (31.6)	
	No. of cylinders	4	4		3		
	Injection type	Indirect Injection	Direct Injection		Direct Injection		
	Total displacement cu.in. (cc)	148.5 (2434)	127.6 (2091)		161.5 (2648)		
	Rated revolution	2700	2600		2300		
	Aspiration	Turbocharged	Turbocharged		Turbocharged		
	Alternator amps	ROPS: 45 // CAB: 60	75		90		
	Fuel tank capacity gal. (l)	13.5 (51)	ROPS: 13.0 (49.2) // CAB: 13.8 (52.2)		16.0 (60.6)		
	Air cleaner	Dual element	Dual element		N/P		
Drive Train	Transmission	3-Range With Hydro Dual Speed Infinitely Variable	12F/12R PowrReverser	3 Range Infinitely Variable	12F/12R	3-Range	
	Brake	Multi-plate wet disc	Multi-plate wet disc		Wet disc		
	PTO	Live Independent	Independent		Independent		
	Engagement method	Electro-hydraulic	Electro-hydraulic		N/P		
	PTO speeds @ RPM	540 @ 2400	540 @ 2600		540 @ 2300		
	Control type	Position (Optional Draft and Mixed)	Position		Position		
	Mid PTO	Optional	N/A		N/P		
	Cruise Control	Standard	N/A	Standard	N/P		
	Creep speed	N/A	N/A				
	Front Axle	Bevel gear	Planetary Gear		N/P		
	Power steering	Hydrostatic power steering	Hydrostatic power steering		Hydrostatic power steering		
	Standard Tires	Front	9.5-16 ; Ag	8-16 ; Ag		9.5-16 ; Ag	
		Rear	14.9-26 ; Ag	14.9-24 ; Ag		14.9-24 ; Ag	
Hydraulic System	Implement Pump capacity gpm (l/m)	9.4 (35.6)	10.2 (38.7)		9.5 (36.0)	9.7 (36.7)	
	Power steering pump gpm (l/m)	4.7 (17.9)	5.7 (21.5)		4.5 (17.0)	5.0 (18.9)	
	Total flow gpm (l/m)	14.1 (53.5)	15.9 (60.2)		14.0 (53.0)	14.7 (55.6)	
	Category hitch	Cat. I & II	Cat. I		Cat. I		
	3-Point Hitch lift capacity @ 24" behind lift point lb. (kg)	2976 (1350)	2500 (1135)		3314 (1503.2), @ pin		
	Rear remote hydraulic valves	Up to 3 rear remotes	Up to 3 rear remotes		1 standard, 2 optional		
	Telescoping link ends	Standard	N/P		Optional		
Stabilizers	Telescoping stabilizers	N/P		Telescoping stabilizers			
Dimensions	Wheelbase in. (mm)	75.4 (1915)	73.0 (1853)		N/P		
	Tread	Front in. (mm)	52.8 (1340)	53.8 (1367)		N/P	
		Rear in. (mm)	52.2 (1325) - 56.3 (1430)	54.0 (1372)		N/P	
	Overall Length w/ 3-Point Hitch in. (mm)	135.0 (3430)	N/P		134.1 (3406)		
	Overall Height in. (mm)	ROPS: 98.0 (2490) // CAB: 92.5 (2350)	ROPS: 100.2 (2546) // CAB: 97.4 (2474)		102 (2590)		
	Overall Width (min. tread) in. (mm)	67.3 (1710)	N/P		71.1 (1807)		
	Min. ground clearance in. (mm)	15.4 (392)	14.8 (377)		N/P		
	Min. turning radius w/ brake ft. (m)	9.2 (2.8)	9.2 (2.8)		11 (3.4)		
	Factory Cab Option	Optional	Optional		Optional		
Weight lbs. (kg)	HST: 4023 (1825) HSTC: 4376 (1985)	ROPS: 3770 (1710) // CAB: 4675 (2120)		ROPS: 4056 (1839.8) // CAB: 4299 (1950)			

N/A = Not Available N/P = Not Published

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.