



**COMPETITIVE COMPARISON**

FEATURE		KUBOTA L47	JCB 3CX Compact	Terramite T9
<b>Engine</b>	Engine gross power (SAEJ 1995)    HP	47.1	74	---
	Engine net power (SAE J 1349)    HP	44.7	---	32.8
	Emissions Tier Level (EPA)	Tier 4 Final	Tier 4 Final	---
	PTO	Standard	No PTO	Not Available
	PTO Power                                    HP	33	No PTO	--
	Fuel Tank Capacity                        gal.	17.7	21	9.5
<b>Drivetrain</b>	Transmission Type	HST	Hydrostatic	HST
	Number of Ranges	6	3	1
	4 Wheel Drive	Standard	Standard	Option
	Max Travel Speed                        mph	14	24.9	---
	Brake	Multi Wet Disk	Multi Wet Disk	---
<b>Hydraulic System</b>	Total hydraulic pump capacity        gal./min	25	26.4	10
	3-Point Hitch lift capacity @ 24" behind lift point    lbs.	2756	No 3-Point	NA
	Position Control	Standard	No 3-Point	NA
	Power Steering	Hydrostatic	Hydrostatic	Hydrastatic



COMPETITIVE COMPARISON					
FEATURE		KUBOTA L47	JCB 3CX Compact	Terramite T9	
Loader	Loader Quick Coupler	Standard	Standard	NA	
	Loader Bucket Capacity	cu. ft.	15.5	24.8	13.5
	Auxiliary Hydraulic Flow	gal./min	11.8	26.4	Option
	Breakout force	lbs.	4531	5,639	6100
	Dump Clearance Full Height	ft. in.	9' 5.9"	10' 5"	--
	Lift capacity @ pivot pin	lbs.	2848	3,364	2300
	Protected Hoses		Standard	Standard	NA
	Auto-Leveling System		Hydraulic	Mechanical	NA
	Standard bucket width	in.	72	78	---
Backhoe	Backhoe Mounting Method	Quick Mount	Permanent	Permanent	
	Maximum Digging Depth	in.	121	120	120
	Max. digging force using bucket cylind lbs.		5825	7363	5200
	Max. digging force using dipperstick cylbs.		3779	6102	3010
	Reach @ Swing Pivot	in.	160.9	13' 1"	--
	Auxiliary Hydraulic Flow	gal./min	11.8	26.4	NA
	Arch Type Boom		Standard	No	Standard
	Bucket QC Option		Available	Available	Available
	Thumb Option		Available	No	NA



COMPETITIVE COMPARISON					
FEATURE		KUBOTA L47	JCB 3CX Compact	Terramite T9	
<b>Features</b>	ROPS/FOPS Canopy	Standard	Standard	---	
	Backup Alarm	Standard	Standard	---	
	Rear Axle Differential Lock	Standard	Optional	---	
	Tilt Steering Wheel	Standard	---	---	
	Retractable Seat Belt	Standard	Standard	---	
<b>Dimensions</b>	Wheelbase	in.	72.5	78	61
	Turning radius with brake	ft.	9.2	19	---
	Min. Ground Clearance	in.	12.3	9	---
	Transport Length	in.	233.9	218	180
	Transport Height	in.	106.3	108	82
	Overall width	in.	72.5	78	60
	Weight with loader, backhoe and ROP lbs.		7205	13382	5000

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.