

M62 TLB



COMPETITIVE COMPARISON

FEATURE		KUBOTA M62	JCB 3CX Compact
Engine	Engine gross power (SAE) HP	63	74
	Engine net power (SAE) HP	59	---
	Emissions Tier Level (EPA)	Tier 4 Final	Tier 4 Final
	PTO	Standard	No PTO
	PTO Power HP	46	No PTO
	Fuel Tank Capacity gal.	17.7	21
Drivetrain	Transmission Type	HST	Hydrostatic
	Number of Ranges	3	3
	4 Wheel Drive	Standard	Standard
	Max Travel Speed mph	15.5	24.9
	Brake	Multi Wet Disk	Multi Wet Disk
Hydraulic System	Total hydraulic pump capacity gal./min.	30.9	26.4
	3-Point Hitch lift capacity @ 24" behind lift point lbs.	2796	No 3-Point
	Position Control	Standard	No 3-Point
	Power Steering	Hydrostatic	Hydrostatic

M62 TLB



COMPETITIVE COMPARISON

FEATURE		KUBOTA M62	JCB 3CX Compact
Loader	Loader Quick Coupler	Standard	Standard
	Loader Bucket Capacity	cu. ft. 23.7	24.8
	Auxiliary Hydraulic Flow	gal./min. 16	26.4
	Breakout force	lbs. 5992	5,639
	Dump Clearance Full Height	ft. in. 10' 6.1"	10' 5"
	Lift capacity @ pivot pin	lbs. 3960	3,364
	Protected Hoses	Standard	Standard
	Auto-Leveling System	Hydraulic	Mechanical
	Standard bucket width	in. 84	78
Backhoe	Backhoe Mounting Method	Quick Mount	Permanent
	Maximum Digging Depth	in. 168	144
	Max. digging force using bucket cylind lbs.	6572	7363
	Max. digging force using dipperstick cy lbs.	4657	6102
	Reach @ Swing Pivot	in. 211.1	13' 1"
	Auxiliary Hydraulic Flow	gal./min. 16	26.4
	Arch Type Boom	Standard	No
	Bucket QC Option	Available	Available
	Thumb Option	Available	No

M62 TLB



COMPETITIVE COMPARISON

FEATURE		KUBOTA M62	JCB 3CX Compact
Features	ROPS/FOPS Canopy	Standard	Standard
	Backup Alarm	Standard	Standard
	Rear Axle Differential Lock	Standard	Optional
	Tilt Steering Wheel	Standard	---
	Retractable Seat Belt	Standard	Standard
Dimensions	Wheelbase	in. 80.7	78
	Turning radius with brake	ft. 10.8	19
	Min. Ground Clearance	in. 13.8	9
	Transport Length	in. 252.9	218
	Transport Height	in. 136	121
	Overall width	in. 75	78
	Weight with loader, backhoe and ROP lbs.	8925	13382

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.