



COMPETITIVE COMPARISON

| MODEL | | Kubota RTV X1140 Worksite | Kawasaki Mule PRO-DXT | Kawasaki Mule 4010Trans 4X4 Diesel | John Deere Gator XUV 855D S4 | Polaris Ranger Crew Diesel |
|--------------|----------------------|---|---------------------------------------|---------------------------------------|---|---|
| Engine | Make | Kubota | n/a | Daihatsu | Yanmar | Kohler |
| | Type | 4-cycle diesel | 4-Cycle diesel | 4-cycle diesel | 4-cycle diesel | 4-cycle diesel |
| | Cylinders | 3 | 3 | 3 | 3 | 3 |
| | Displacement (cc) | 1123 | 993 | 953 | 854 | 1028 |
| | Horsepower | 24.8hp | n/a | 24.7hp | 22.5hp | 24 |
| | Torque (lbs/ft) | 52.7 | 38 | 52 | 50 | n/a |
| Fuel System | Fuel Tank Capacity | 7.9 gallons | 7.9 gallons | 6.4 gallons | 7 gallons | 10 gallons |
| Muffler | | Spark arresting | Spark arresting | Spark arresting | Spark arresting | Spark arresting |
| Alternator | | 60 amps | 55 amps | 40 amps | 55 amps | 110 amps |
| Transmission | Type | Variable Hydrostatic Transmission (VHT-X) | CVT with belts | CVT with belts | CVT with belts | CVT with belts |
| | Wheels, drive system | Rear 2WD or 4WD | Rear 2WD or 4WD | Rear 2WD or 4WD | On demand 4WD | Rear 2WD or 4WD |
| | Differential Lock | Standard, foot operated | Switch activated/ Rear axle only | Rear, dual-mode | Front- on/off switch Rear-hand operated | Front- on/off switch Rear-hand operated |
| | Gear Selection | Hi-Lo range forward, neutral, reverse | Hi-Lo range forward, neutral, reverse | Hi Lo range forward, neutral, reverse | Hi-Lo range forward, neutral, reverse | Hi-Lo range forward, neutral, reverse, park |
| Steering | | Power full hydraulic with manual tilt feature | Manual with tilt (EPS optional) | Power-electric | Power-electric | Manual steering with tilt |



COMPETITIVE COMPARISON

| MODEL | | Kubota RTV X1140 Worksite | Kawasaki Mule PRO-DXT | Kawasaki Mule 4010Trans 4X4 Diesel | John Deere Gator XUV 855D S4 | Polaris Ranger Crew Diesel |
|----------------------------|---------|---|---|---|------------------------------|----------------------------|
| Brakes | Front | Sealed hydraulic discs | hydraulic disc | hydraulic drums | hydraulic disc | hydraulic disc |
| | Rear | Sealed hydraulic discs | hydraulic disc | hydraulic drums | hydraulic disc | hydraulic disc |
| | Parking | rear wheel, hand lever | rear wheel, hand lever | rear wheel, hand lever | driveline, hand lever | Park in transmission |
| Suspension | Front | Independent, dual A-arms | Double wishbone | Independent, McPherson struts | Dual A-arm | Dual A-arm |
| | Rear | Independent with coil over shock | Double wishbone | Semi-independent DeDion axle w/ leaf springs and hydraulic shocks | Dual A-arm | Dual A-arm |
| Front Guard | | Standard | Standard | Standard | Standard | Standard |
| Occupant Protection System | | 2.0 Steel tube: meets OSHA 1928.53 & SAE J2194 ROPS | ROPS meets the performance requirements of ISO 3471 | Steel tube ROPS meets SAE J1194 | ROPS certified | Steel tube ROPS |
| Seating | | Digital Multi-meter | Digital Multi-meter | Speedometer & gauges | Digital Multi-meter | Digital Multi-meter |



COMPETITIVE COMPARISON

| MODEL | | Kubota RTV X1140 Worksite | Kawasaki Mule PRO-DXT | Kawasaki Mule 4010Trans 4X4 Diesel | John Deere Gator XUV 855D S4 | Polaris Ranger Crew Diesel |
|---|------------------------------|--|--|---|---|--|
| Factory-installed Integrated Full Cabin | | Bench Seats - Convertible 1 to 2 row seating | Bench Seats - Convertible 1 to 2 row seating | Bench Seats- Convertible 1 to 2 row seating | Bucket seats - Non-convertible, fixed 2 row seating | Bench Seats - Non-convertible, fixed 2 row seating |
| Factory Air Conditioner, Heater & Defroster | | not available | not available | not available | not available | not available |
| Speaker system | | -- | | -- | -- | -- |
| Standard pre-wiring for optional stereo | | -- | -- | -- | -- | -- |
| Sound level, @ operator's ear | At max speed w/ no load | 84dBA | -- | -- | -- | -- |
| | At 15 mph | -- | -- | -- | -- | -- |
| Overall Dimensions (inches) | Length | 143.3 | 133.2 | 116.7 | 154 | 148.5 |
| | Width | 62.2 | 64 | 62 | 62 | 61 |
| | Height, overall | 80.1 | 77.6 | 75.8 | 75 | 76 |
| | Front tread centers | 50.4 | n/a | 45.7 | 51.2 | n/a |
| | Rear tread centers | 50.4 | n/a | 46.5 | 51.2 | n/a |
| | Wheelbase | 98.2 | 92.3 | 73.6 | 114 | 113 |
| | Ground clearance, front axle | 10.8 | TBA - 10" min | 6.9 | 11 | 11.3 |
| | Ground clearance, rear axle | 9.3 | TBA - 10" min | 8.3 | 11 | 11.3 |



COMPETITIVE COMPARISON

| MODEL | | Kubota RTV X1140 Worksite | Kawasaki Mule PRO-DXT | Kawasaki Mule 4010Trans 4X4 Diesel | John Deere Gator XUV 855D S4 | Polaris Ranger Crew Diesel |
|------------------------|---|--------------------------------|------------------------------------|------------------------------------|------------------------------|----------------------------|
| Turning radius (ft) | | 17.7 | 16 | 12.5 | 28.3 | 17.8 |
| Payload Capacity (lbs) | | 1629 | 1616 | 1632 | 1400 | 1750 |
| Towing Capacity (lbs) | | 1301 | 2000 | 1200 | 1500 | 2000 |
| Tow Hitch Availability | | Standard 2" front & rear | Standard 2" rear | Standard 2" rear | Standard 2" rear | Standard 2" rear |
| Vehicle weight (lbs) | | 2370 | 1889.7 | 1738 | 2018 | 1690 |
| Cargo Bed | Bed Load Capacity (lbs) 1 row or 2 row mode | 1102lbs - 1 row 661lbs - 2 row | 1000 lb - 1 row 350 lb 2 row | 800 lb -1 row 400 lb - 2 row | 1000 | 1000 |
| | Bed Lift System | hydraulic | Strut assist (Optional Hydraulic) | manual | manual | manual |
| | Width x Length x Depth (in.) 1 row mode | 57.7 x 51.6 x 11.2 | 53.7 x 42.7 x 11 | 47.7 x 50.4 x 11.3 | -- | -- |
| | Width x Length x Depth (in.) 2 row mode | 57.7 x 26 x 11.2 | 53.7 x 22 x 11 | 47.7 x 30.0 x 11.3 | 52 x 45 x 11 | 54 x 36.5 x 11.5 |
| | Volume (cu ft) 1 or 2 row | 19.1 Long 9.9 Short | 14.6 / 7.5 | 15.6 / 9.4 | 16.2 | 13.1 |
| Tire Selection | | Heavy Duty Worksite or ATV | Duro | N/P | Ancla M-T or Maxxis Big Horn | PXT |



COMPETITIVE COMPARISON

| MODEL | | Kubota RTV X1140 Worksite | Kawasaki Mule PRO-DXT | Kawasaki Mule 4010Trans 4X4 Diesel | John Deere Gator XUV 855D S4 | Polaris Ranger Crew Diesel |
|-------|-------|------------------------------|--------------------------|--|---------------------------------|-------------------------------|
| Tires | Front | 25x10-13 | 26 x 9-12 | 23x11-10 | 26x9-12 or 27 x 9-14 | 26 x 9-12 |
| | Rear | 25x10-13 | 26 x 11-12 | 23x11-10 | 26x11-12 or 27x11-14 | 26 x 11-12 |

Comparisons of specifications are based on the latest data available to Kubota at the time of publication.

Kubota reserves the right to change specifications relating to its products without notice.

Competitive information in this section was obtained from competitive websites and product brochures, and is correct to the best of our knowledge.

* Manual-tilt feature for steering wheel and fore/aft adjustment for driver's seat is not available on RTV-X900 General Purpose models