

FEATURES		COMPETITIVE COMPARISON						
		Kubota SSV65	Bobcat S570	New Holland L218	Deere 318G	CASE SV185	CAT 232D	
Engine	Engine Brand	Kubota	Doosan	ISM	Yanmar	ISM	CAT	
	Engine Model	V2607-CR-TE4	np	N844LTA-DI-F-50	4TNV86 CHT	N844LTA-DL-F-45	C2.2 CRDI	
	Emission	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	
	Emission Solution	DPF	DOC	DOC	DPF	DOC	DOC	
	Gross Engine (*SAE J1995)	HP (kW)	64 (47.7)*	61	60 (45)	65 (48.5)	60 (44.7)	65.8 (49)
	Peak Torque	lb-ft (N-m)	166 (225)	np	135 (183)	158 (214)	153 (208)	153 (207)
	Displacement	cu in(L)	159.7 (2.6)	147.4 (2.4)	135.2 (2.2)	128 (2.1)	135.2 (2.2)	134.3 (2.2)
	Cylinders		4	4	4	4	4	4
	Aspiration		Turbo	Turbo	Turbo	Turbo	Turbo	Turbo
Loader Specifications	Geometry	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical	
	Tipping Load	lbs (kg)	3900 (1770)	3900 (1770)	3600 (1633)	3890 (1776)	3700 (1680)	3700 (1770)
	Rated Operating Capacity (35% of tipping)	lbs (kg)	1950 (885)	1950 (885)	1800 (818)	1945 (883)	1850 (840)	1850 (839)
	Tip Breakout	lbs (kg)	4839 (2195)	np	5550 (2495)	6000 (2724)	5550 (2495)	3984 (1807)
	Lift Breakout	lbs (kg)	3858 (1750)	np	3450 (1565)	5000 (2270)	3450 (1565)	np
Hydraulic Lift Capacity	lbs (kg)	4409 (2000)	np	3600 (1633)	np	3700 (1678)	np	
Drive Train	Standard Tire Size	10-16.5-8PR	10-16.5-8PR	10-16.5-8PR	10-16.5-8PR	10-16.5-8PR	10-16.5-8PR	
	Chain Size ASA#	80	80	80	np	80	np	
	Travel Speed Low Gear	mph (kph)	6.9 (11.1)	7.4 (11.9)	7.4 (11.9)	6.9 (11.1 km)	7.4 (11.9)	7.6 (12.2)
	Travel Speed High Gear	mph (kph)	11.1 (17.9)	11.0 (17.7)	10.8 (17.4)	10.1 (16.3)	10.8 (17.4)	11.1 (17.9)
Hydraulic Systems	Pump Flow Standard	gpm (lpm)	18.0 (68.0)	17.1 (65)	20.6 (78)	16 (59)	20.6 (78)	18.0 (68)
	Pump Flow Optional High Flow	gpm (lpm)	28.0 (106.0)	26.7 (102)	30.7 (116.2)	n/a	30.7 (116.2)	26.0 (98.4)
	Hydraulic Pressure	psi (bar)	3271 (230)	3500 (242)	3000 (207)	3450 (243)	3000 (207)	3336 (230)
Dimensions	Height to Top of ROPS	in (mm)	79.9 (2029)	77.8 (1976)	78.7 (1998)	77.2 (1960)	77.5 (1970)	79.9 (2029)
	Overall Length with Standard Bucket	in (mm)	135.4 (3439)	133 (2979)	131.4 (3338)	127.6 (3240)	131.7 (3345)	127.3 (3233)
	Length w/o Bucket	in (mm)	106.3 (2700)	104.6 (2343)	105.7 (2685)	103 (2630)	105.7 (2685)	99.3 (2522)
	Width over Tires	in (mm)	66.5 (1689)	64.7 (1449)	66 (1676)	62.9 (1600)	66 (1676)	58.9 (1496)
	Width with Standard Bucket	in (mm)	68.8 (1746)	68 (1523)	66 (1676)	66.0 (1478)	66 (1676)	60.0 (1524)
	Wheelbase	in (mm)	44.3 (1125)	42.6 (954)	44.4 (1130)	41.5 (1050)	44.4 (1130)	41.5 (1054)
	Dump Clearance at Full Height	in (mm)	92.4 (2347)	np	94.7 (2405)	94.3 (2400)	93.7 (2380)	88.7 (2253)
	Height to Bucket Pin	in (mm)	121.5 (3085)	119 (2666)	121 (3073)	120 (3050)	120 (3048)	118.1 (3000)
	Reach at Max Dump Height	in (mm)	32.7 (831)	32.6 (730)	29.8 (758)	34 (860)	30.7 (780)	25.7 (653)
	Bucket Rollback at Ground	degrees	27	np	34.4	30	35	np
	Max Dump Angle at Full Height	degrees	38	np	51.9	42	51.9	47.4
	Rear Angle of Departure		23.9	np	25	22.3	23	27.9
	Ground Clearance	in (mm)	7.9 (201)	np	7 (178)	7 (180)	7 (178)	6.7 (170)
Operating Weight	lbs (kg)	6790 (3080)	6480 (2945)	5930 (2690)	6475 (2940)	6570 (2980)	6213 (2818)	
Service Capacities	Fuel Tank	gal (l)	25.4 (96.0)	24.75 (93.9)	19.9 (75.5)	19 (71)	19.9 (75.5)	15.1 (57)
	Hydraulic Tank	gal (l)	4.2 (16.0)	np	4.3 (16.3)	np	4.3 (16.3)	9.0 (34.0)

NA = Not Available

NP = Not Published

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



FEATURES		COMPETITIVE COMPARISON					
		Kubota SSV75	Bobcat S650	New Holland L228	Cat 262D	Deere 324E	CASE SV280
Engine	Engine Brand	Kubota	Doosan	FPT	CAT	Yanmar	FPT
	Engine Model	V3307-CR-TE4	np	F5H FL463	C3.3B DIT	4TNV98CT	F5H FL463
	Emission	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4
	Emission Solution	DPF	DOC	PMC	np	DPF	PMC
	Gross Engine (*SAE J1995) HP (kW)	74.3 (55.4)*	74 (55)	74 (55)	74 (55)	74 (55)	74 (55)
	Peak Torque lb-ft (N-m)	196 (265)	np	232 (314)	np	207 (280)	232 (314)
	Displacement cu in(L)	203 (3.3)	147.4 (2.4)	207 (3.4)	203 (3.3)	201 (3.3)	207 (3.4)
	Cylinders	4	4	4	4	4	4
	Aspiration	Turbo	Turbo	Turbo	Turbo	Turbo	Turbo
Loader Specifications	Geometry	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical
	Tipping Load lbs (kg)	5380 (2440)	5380 (2440)	5600 (2540)	5400 (2449)	5380 (2440)	5600 (2540)
	Rated Operating Capacity (35% of tipping) lbs (kg)	2690 (1220)	2690 (1220)	2800 (1270)	2700 (1224)	2690 (1221)	2800 (1270)
	Tip Breakout lbs (kg)	5884 (2669)	np	8620 (3910)	7355 (3336)	8750 (3870)	7570 (3433)
	Lift Breakout lbs (kg)	4850 (2200)	np	6030 (2735)	np	5500 (2517)	5530 (2508)
	Hydraulic Lift Capacity lbs (kg)	5452 (2473)	np	5832 (2645)	np	np	5983 (2714)
Drive Train	Standard Tire Size	12x16.5-8PR	12x16.5-12PR	12-16.5-8PR	12x16.5 10 PR	12x16.5-10PR	12-16.5-8PR
	Chain Size ASA#	100	np	100	np	80	100
	Travel Speed Low Gear mph (kph)	7.1 (11.4)	7.1 (11.5)	7.0 (11.3)	7.7 (12.3)	6.9 (11.1)	7.0 (11.3)
	Travel Speed High Gear mph (kph)	11.4 (18.3)	12.3 (19.9)	10.5 (16.9)	11 (17.7)	11.1 (17.9)	10.5 (16.9)
Hydraulic Systems	Pump Flow Standard gpm (lpm)	20.9 (79.0)	23 (87)	24.2 (91.5)	23 (87)	21 (79)	24.2 (91.5)
	Pump Flow Optional High Flow gpm (lpm)	30.4 (115.0)	30.5 (115.3)	37.3 (142.5)	32 (121)	29 (110)	37.3 (142.5)
	Hydraulic Pressure psi (bar)	3271 (225)	3500 (242)	3000 (207)	3335 (230)	3450 (238)	3000 (207)
Dimensions	Height to Top of ROPS in (mm)	81.3 (2065)	81.3 (2065)	78.8 (2002)	83.1 (2110)	79.4 (2020)	78.8 (2002)
	Overall Length with Standard Bucket in (mm)	144.1 (3660)	136.8 (3473)	142.9 (3631)	146.2 (3713)	136.8 (3470)	141.9 (3604)
	Length w/o Bucket in (mm)	115.0 (2920)	108.4 (2752)	117.8 (2993)	117.9 (2994)	112 (2850)	117.7 (2990)
	Width over Tires in (mm)	71.8 (1823)	72.1 (1831)	69.6 (1768)	66.0(1676)	70.1 (1780)	69.6 (1768)
	Width with Standard Bucket in (mm)	74.8 (1899)	74 (1879)	72.0 (1829)	66.0(1676)	76 (1930)	72.0 (1829)
	Wheelbase in (mm)	98.0 (1210)	45.3 (1150)	52 (1322)	49.2 (1249)	44.3 (1130)	52 (1322)
	Dump Clearance at Full Height in (mm)	98.0 (2490)	np	102.9 (2615)	93.7 (2381)	100.9 (2560)	103.5 (2629)
	Height to Bucket Pin in (mm)	128.3 (3258)	124.3 (3157)	129.4 (3287)	124.9 (3172)	125.5 (3190)	130 (3302)
	Reach at Max Dump Height in (mm)	36.9 (936)	31.5 (800)	32.3 (821)	30.9 (784)	36.3 (920)	26.4 (672)
	Bucket Rollback at Ground degrees	27	np	33.6	np	33	35
	Max Dump Angle at Full Height degrees	40	np	54.7	51	43	53.5
	Rear Angle of Departure	24.6	np	23.5	26	25	23.5
	Ground Clearance in (mm)	8.5 (217)	np	8.0 (203)	8.9 (226)	8.5 (217)	8.0 (203)
Operating Weight lbs (kg)	8157 (3700)	8061 (3664)	8245 (3770)	8011 (3633)	7500 (3405)	8090 (3670)	
Service Capacities	Fuel Tank gal (l)	26.9 (102.0)	27.5 (104)	25.5 (96.5)	24.8 (94)	20 (76)	25.5 (96.5)
	Hydraulic Tank gal (l)	4.2 (16.0)	np	6 (22.5)	10.3 (38.9)	np	6 (22.5)

NA = Not Available

NP = Not Published

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.