

Specifications

Model	L3302				L3902			
	Gear-Drive Transmission		HST		Gear-Drive Transmission		HST	
	4WD		4WD		4WD		4WD	
Engine								
Type	Direct injection, vertical, water-cooled 4-cycle diesel							
Engine gross power*	HP (kW)	33.0 (24.6)			37.5 (28.0)			
Engine net power**	HP (kW)	31.8 (23.7)			36.3 (27.1)			
PTO power	HP (kW)	28.0 (20.9)	26.1 (19.5)		32.1 (23.9)		30.3 (22.6)	
No. of cylinders	3							
Bore & stroke	in. (mm)	3.4 × 4.0 (87 × 102.4)						
Total displacement	cu. in. (cm ³)	111.4 (1826)						
Rated speed	rpm	2700						
Battery	12V, RC: 110 min, CCA: 580 A		12V, RC: 120 min, CCA: 600 A		12V, RC: 110 min, CCA: 580 A		12V, RC: 120 min, CCA: 600 A	
Alternator	12V, 45A							
Fuel tank capacity	US gal. (ℓ)	11.1 (42)						
PTO								
Rear PTO type	Transmission driven with overrunning clutch		Live independent PTO with hydraulic clutch		Live - continuous running		Live independent PTO with hydraulic clutch	
PTO/Engine speed	540/2430		540/2470		540/2425		540/2470	
Hydraulic								
Lift control type	Position control							
Pump capacity (main)	gpm (ℓ/min)	6.8 (25.7)						
(PS)	gpm (ℓ/min)	4.1 (15.6)						
3-point hitch	SAE Category I							
Lift capacity at lift points	lbs. (kg)	1985 (900)						
24 in. behind lift points	lbs. (kg)	1433 (650)						
System pressure	kgf/cm ² (MPa)	165 (16.2)						
Traveling system								
Transmission	Gear shift with synchronized shuttle, 8 forward and 8 reverse		Hydrostatic transmission, 3 range speed		Gear shift with synchronized shuttle, 8 forward and 8 reverse		Hydrostatic transmission, 3 range speed	
Steering	Integral type power steering							
Brake	Mechanical, wet disc type							
Clutch	Dry type single stage		—		Dry type dual stage		—	
Tire size								
AG standard	Front/Rear	7.0 - 16 / 11.2 - 24						
TURF option	Front/Rear	25 × 8.50-14 / 13.6-16						
Indust. option	Front/Rear	27 × 8.50 - 15 / 15 - 19.5 R4						
AG/Indust. hybrid option	Front/Rear	27 × 8.50 - 15 R14 / 15 - 19.5 R4						
Traveling speed with standard AG tires								
	mph (km/h)	Forward 1.1 (1.7) - 13.2 (21.2) Reverse 1.1 (1.7) - 13.2 (21.2)	Forward 0.0 (0.0) - 14.1 (22.7) Reverse 0.0 (0.0) - 12.7 (20.5)	Forward 1.1 (1.7) - 13.2 (21.2) Reverse 1.1 (1.7) - 13.2 (21.2)	Forward 0.0 (0.0) - 14.1 (22.7) Reverse 0.0 (0.0) - 12.7 (20.5)			
Dimensions								
Overall length (w/o 3P)	in. (mm)	108.7 (2760)						
Overall width (min. tread)	in. (mm)	55.1 (1400)						
Overall height (w/Foldable ROPS)	in. (mm)	91.7 (2330)						
Wheelbase	in. (mm)	63.4 (1610)						
Min. ground clearance	in. (mm)	13.4 (340)						
Tread Front tire	in. (mm)	43.1 (1095)						
Rear tire	in. (mm)	43.9 (1115) / 47.1 (1195) / 50.8 (1290)						
Min. turning radius (w/brake, 4WD disengaged)	feet (m)	8.2 (2.5)						
Weight (with ROPS)	lbs. (kg)	2833 (1285)	2899 (1315)	2866 (1300)	2899 (1315)			

* SAE J1995 ** SAE J1349

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



KUBOTA TRACTOR CORPORATION

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: kubotaUSA.com

©2022 Kubota Corporation



Standard L

Specifications

L2501



Model			L2501		
			Gear-Drive Transmission		HST
			2WD	4WD	4WD
Engine	Type				
	Engine gross horsepower*	HP (kW)	24.8 (18.5)		
	Engine net power**	HP (kW)	23.9 (17.8)		
	PTO power	HP (kW)	20.5 (15.3)		19.0 (14.2)
	No. of cylinders		3		
	Bore & stroke	in. (mm)	3.4 x 3.6 (87 x 92.4)		
	Total displacement	cu. in. (cm3)	100.47 (1647)		
	Rated speed	rpm	2200		
	Battery		12V, RC: 123 min, CCA: 490 A		
	Alternator				
	Fuel tank capacity	US gal. (t)	10.0 (38.0)		
PTO	Rear PTO type		Transmission driven with overrunning clutch		Live-continuous running
	PTO/Engine speedsystem		540/1910		540/2105
Hydraulic	Lift control type				
	Pump capacity (main)	gpm (l/min)	5.15 (19.5)		
	(PS)	gpm (l/min)	3.13 (11.8)		
	3-point hitch				
	Lift capacity at lift points	lbs. (kg)	1918 (870)		
	24 in. behind lift points	lbs. (kg)	1389 (630)		
	System pressure	kgf/cm2 (MPa)	2205 (15.2)		
Traveling System	Transmission		Gear shift, 8 forward and 4 reverse		Hydrostatic transmission, 3 range speed
	Steering		Integral type power steering		
	Brake		Wet disc type		
	Clutch		Dry type single stage		
Tire size	AG Standard		5 - 15/ 11.2 - 24	7.2 - 16/ 11.2 - 24	
	TURF Option	Front/Rear	N / A		
	Indust. Option	Front/Rear	N / A	27 x 8.50 - 15/ 15 - 19.5 R4	
Traveling speed with standard AG tires		mph (km/h)	Forward 0.9 (1.4) - 10.7 (17.3) Reverse 1.2 (1.9) - 3.9 (6.2)		Forward 0 (0.0) - 11.5 (18.5) Reverse 0 (0.0) - 10.3 (16.6)
Dimensions	Overall length (w/o 3P)	in. (mm)	110.6 (2810)	106.3 (2700)	
	Overall width (min.tread)	in. (mm)	55.1 (1400)		
	Overall height (w/Foldable ROPS)	in. (mm)			
	Wheelbase	in. (mm)	63.3 (1610)		
	Min. ground clearance	in. (mm)	13.6 (345) 13.4	13.4 (340)	
	Tread	Rear tire in. (mm)	41.3 (1050)	43.1 (1095)	
		Front tire in. (mm)	43.8 (1115) / 47.1 (1195) / 50.8 (1290)		
	Min. turning radius (w/brake, 4WD disengaged)	feet (m)	7.9 (2.4)	8.2 (2.5)	
Weight (with ROPS)		lbs. (kg)	2425 (1100)	2601 (1180)	2623 (1190)

* SAE J1995

** SAE J1349

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

Standard L

Specifications

L3301 - L3901 - L4701



Model	L3301			L3901			L4701			
	Gear-Drive Transmission		HST	Gear-Drive Transmission		HST	Gear-Drive Transmission		HST	
	2WD	4WD	4WD	2WD	4WD	4WD	2WD	4WD	4WD	
Engine										
Type	Direct injection, vertical, water-cooled 4-cycle diesel									
Engine gross power*	HP (kW)	33.0 (24.6)			37.5 (28.0)			47.3 (35.2)		
Engine net power**	HP (kW)	31.4 (23.4)			36.3 (27.1)			44.8 (33.4)		
PTO power	HP (kW)	27.7 (20.7)	26.2 (19.5)	32.1 (23.9)	30.6 (22.8)	39.3 (29.3)	37.8 (28.2)			
No. of cylinders		3						4		
Bore & stroke	in. (mm)	3.4 × 4.0 (87 × 102.4)								
Total displacement	cu. in. (cm ³)	111.4 (1826)						148.5 (2434)		
Rated speed	rpm	2700						2600		
Battery		12V, RC: 110 min, CCA: 580 A						12V, RC: 120 min, CCA: 600 A		
Alternator		12V, 40A								
Fuel tank capacity	US gal. (ℓ)	11.1 (42)						13.5 (51)		
PTO										
Rear PTO type		Transmission driven with overrunning clutch	Live - with overrunning clutch	Live-continuous running	Live - with overrunning clutch	Live-independent hydraulic PTO with PTO brake, wet clutch				
PTO/Engine speed		540/2430	540/2580	540/2425	540/2580	540/2475	540/2640			
Hydraulic										
Lift control type		Position control								
Pump capacity (main)	gpm (ℓ/min)	6.1 (45.1)			6.8 (25.7)			8.4 (31.7)		
(PS)	gpm (ℓ/min)	4.1 (15.6)			4.1 (15.6)			5.1 (19.2)		
3-point hitch		Category I								
Lift capacity at lift points	lbs. (kg)	1985 (900)						2870 (1300)		
24 in. behind lift points	lbs. (kg)	1433 (650)						2320 (1053)		
System pressure	kgf/cm ² (MPa)	165 (16.2)						180 (17.7)		
Traveling System										
Transmission		Gear shift with synchronized shuttle, 8 forward and 8 reverse	Hydrostatic transmission, 3 range speed	Gear shift with synchronized shuttle, 8 forward and 8 reverse	Hydrostatic transmission, 3 range speed	Constant mesh with synchronized shuttle 8 forward and 8 reverse	Hydrostatic transmission, 3 range speed			
Steering		Integral type power steering						Hydrostatic power steering		
Brake		Mechanical, wet disc type								
Clutch		Dry type single stage			Dry type dual stage	Dry single	Dry type single stage	No clutch		
Tire size										
AG Standard	Front/Rear	5.00 - 15/11.2 - 24	7.2 - 16/11.2 - 24	5.00 - 15/11.2 - 24	7.2 - 16/11.2 - 24	7.5L - 15/14.9 - 24	8.3 - 16/14.9 - 24			
TURF Option	Front/Rear	23 × 8.50-12 13.6-16	25 × 8.50-14/13.6-16	23 × 8.50-12 13.6-16	25 × 8.50-14/13.6-16	27 × 8.50 - 15 44 × 18 - 20	27 × 10.5/44 × 18 - 20, 27 × 8.50 - 15 44 × 18 - 20, 305R343L3SW / 44 × 18 - 20			
Indust. Option	Front/Rear	N/A	27 × 8.50 - 15/15 - 19.5 R4	N/A	27 × 8.50 - 15/15 - 19.5 R4	N/A	10.0 - 16.5 / 17.5L - 24			
Traveling speed with standard AG tires										
	mph (km/h)	Forward 1.1 (1.7) - 13.2 (21.2) Reverse 1.1 (1.7) - 13.1 (21.1)	Forward 0.0 (0.0) - 14.1 (22.7) Reverse 0.0 (0.0) - 12.7 (20.5)	Forward 1.1 (1.7) - 13.2 (21.2) Reverse 1.1 (1.7) - 13.1 (21.1)	Forward 0.0 (0.0) - 14.1 (22.7) Reverse 0.0 (0.0) - 12.7 (20.5)	Forward 1.4 (2.2) - 14.9 (24.0) Reverse 1.3 (2.1) - 14.3 (23.0)	Forward 0.0 (0.0) - 15.8 (25.4) Reverse 0.0 (0.0) - 14.2 (22.9)			
Dimensions										
Overall length (w/o 3P)	in. (mm)	110.6 (2810)	107.9 (2740)	110.6 (2810)	107.9 (2740)	122.8 (3120)	119.5 (3035)			
Overall width (min. tread)	in. (mm)	55.1 (1400)						62.4 (1585)		
Overall height (w/Foldable ROPS)	in. (mm)	91.7 (2330)								
Wheelbase	in. (mm)	63.3 (1610)						72.8 (1850)	72.6 (1845)	
Min. ground clearance	in. (mm)	13.6 (345)	13.4 (340)	13.6 (345)	13.4 (340)	15.2 (385)				
Tread										
Front tire	in. (mm)	41.3 (1050)	43.1 (1095)	41.3 (1050)	43.1 (1095)	50.4 (1280) 54.3 (1380) 58.3 (1480) 62.2 (1580)	45.5 (1155)			
Rear tire	in. (mm)	43.8 (1115) / 47.1 (1195) / 50.8 (1290)						46.5 (1180), 47.2 (1200), 51.2 (1300), 57.1 (1450), 60.8 (1545)		
Min. turning radius (w/brake, 4WD disengaged)	feet (m)	7.9 (2.4)	8.2 (2.5)	7.9 (2.4)	8.2 (2.5)	8.9 (2.7)	8.5 (2.6)			
Weight (with ROPS)	lbs. (kg)	2557 (1160)	2734 (1240)	2778 (1260)	2590 (1175)	2767 (1255)	2778 (1260)	3219 (1460)	3296 (1495)	3307 (1500)

* SAE J1995

** SAE J1349

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.